

Secure-Grip Flange Spreader Set, 110 kN, 90 mm Max. Spread - Enerpac SG11TMSTD

Item no. ENP-SG11TMSTD

Manufacturer Enerpac

SG11TM Secure-Grip flange spreader delivering up to 110 kN (220 kN in a pair) for bolt holes from 30 to 39 mm.

TECHNICAL DATA

Country of Manufacture	United States
Hinweis	Verschraubungsgeräte
Kapazität (kN)	100-250 kN
Serie	SG
Weight	20 kg



DESCRIPTION

The SG11TM Secure-Grip flange spreader safely parts bolted flanges and delivers up to 110 kN (12,3 tons) of spreading force, up to 220 kN when used in the recommended pair. Mechanical drive through a torque wrench needs no hydraulic power pack.

BENEFITS

- Positive collet grip in bolt holes from 30 to 39 mm prevents the tool from slipping
- Adjustable drive cones spread flanges and free spacers, wafers or butterfly valves
- Up to 110 kN of spreading force on its own, 220 kN in a pair
- Mechanical torque-wrench drive, no hydraulic power pack needed
- Collet holders can be dismantled and inserted through the bolt holes from the opposite side

TECHNICAL DATA

- Spreading force: 110 kN (12.3 tons)
- Spreading force in a pair: 220 kN
- Bolt-hole range: 30 - 39 mm
- Max. spread: 90 mm
- Drive: mechanical (torque wrench)
- Weight: 20 kg
- Series: SG

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

IN THE BOX

- SG11TM tool
- 150 mm vernier calliper
- 1/2" drive torque wrench with 24 mm socket
- safety block
- M30, M33 and M36 collets (2 each)
- instruction manual and carry case with foam inserts