

Push-in L-fitting »click-clock« rotating, M5 o., hose exterior Ø5 - Riegler 108633

Item no. RGL-108633

Manufacturer Riegler

EAN 4047322292214

Push-in L-fitting »click-clock« rotating, M5 o., hose exterior Ø5

TECHNICAL DATA

Betriebsdruck max [bar]	16.000000
Country of Manufacture	Italy
For hose OD [mm]	5
Material	Nickel-plated brass
Medium	Compressed air
Norm	DIN 13-1, DIN EN ISO 228-1
Pneumatic connection	M5 AG
Seal material	NBR
Series	click-clock
Temperature (max.)	80
Thread	M5 AG
Weight	0.015 kg
Working pressure max. [bar]	16
Zolltarifnummer	74122000



STANDARDS & COMPLIANCE

ISO 7-1 ISO 228-1 DIN 13-1

DESCRIPTION

Push-in L-fitting »click-clock«, rotating, M5 o., for hose exterior Ø 5 mm, Working pressure -0.99 to 16 bar, nickel-plated brass The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting Can also be used for non-calibrated hoses Suitable for vacuum operation

TECHNICAL DATA

Series	click-clock
Min. working pressure	-0.99 bar
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Max. operating temperature	80 °C
Material	nickel-plated brass

A1-ESD equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

fluidics-equipment.com

Page 1/3

Sealant	NBR
Medium	compressed air
Recommended hose	PA, PU
Applications	compressed air systems, vacuum
Sleeve	hostaform
Clamping ring	stainless steel
Thread	M5 ET
for tube O.D.	5 mm
L1	24.0 mm
L2	19.0 mm
a/f	2 mm

STANDARDS AND ORIGIN

- Customs tariff number: 74122000
- Country of origin: IT

ABOUT MALE ELBOWS

Push-in L-fittings turn a tube line through 90 degrees and remove the need for a separate elbow ahead of the consumer. The range accepts tube outside diameters from 3 to 16 mm and works up to 10 to 20 bar depending on version. The lower limit goes down to -0.99 bar, so vacuum lines can be built with the same parts.

WHAT MATTERS WHEN CHOOSING

- Thread: The range covers G 1/8 to G 1/2 male, tapered R 1/8 to R 1/2 male, metric M3, M5 and M6 male plus G 1/4 female. Versions with two ports list thread 1 from G 1/8 to G 1/2 female and thread 2 from G 1/8 male to R 1/2 male separately.
- For tube O.D.: The figure of 3 to 16 mm refers to the outside diameter of the tube, not to the nominal bore. It has to match the tube exactly, otherwise the collet loses its grip.
- Working pressure: The upper limit sits between 10 and 20 bar, the lower limit between -0.99 and 0 bar. Vacuum work calls for the version with the negative lower limit.
- Material and sealant: Plastic with nickel-plated brass, all nickel-plated brass and stainless steel 1.4404 are available, sealed with NBR, FKM or FPM, or FKM or FPM in an FDA-compliant version.
- Medium and series: Besides compressed air, the data covers water, neutral gases and liquids, oil and grease as well as corrosive media within the limits of material compatibility. Series range from Blue Series and Blue Series mini through click-clock, metallica and universal short to inox line and NonPlusUltra.

TYPICAL APPLICATIONS

- Connecting pneumatic cylinders where a straight outlet leaves no room at the end cap.
- Piping valve manifolds and control blocks with tight bend radii.
- Vacuum lines on suction cups and handling equipment.

- Plants with wash-down cycles, where stainless steel 1.4404 faces splash water and cleaning agents.
- Filling and packaging lines that need an FDA-compliant seal close to the product.

Thread standards ISO 7-1, DIN EN ISO 228-1 and DIN 13-1 are recorded for part of the 445 items. Operating temperature is given as -20 °C at the low end and, depending on material, 80 to 150 °C at the top.