

Push-in L-fitting R 1/4 o., for hose exterior Ø 10, ES 1.4404 - Riegler 135162

Item no. RGL-135162

Manufacturer Riegler

EAN 4047322493703

Push-in L-fitting R 1/4 o., for hose exterior Ø 10, ES 1.4404

TECHNICAL DATA

Betriebsdruck max [bar]	20.000000
Country of Manufacture	India
For hose OD [mm]	10
Material	Stainless steel 1.4404
Medium	Compressed air, corrosive media (if compatible with the material)
Norm	DIN 13-1, DIN EN ISO 228-1
Pneumatic connection	R1/4 AG
Seal material	FKM, FPM
Series	inox line
Temperature (max.)	150
Thread	R 1/4 AG
Thread standard	ISO 7-1
Weight	0.047 kg
Working pressure max. [bar]	20
Zolltarifnummer	73072910



STANDARDS & COMPLIANCE

ISO 7-1 ISO 228-1 DIN 13-1

DESCRIPTION

Push-in L-fitting, R 1/4 o., for hose exterior Ø 10 mm, Working pressure -0.98 - 20 bar, Stainless steel 1.4404 For use in more aggressive environments and corrosive media. The suitability test for the individual application is the user's responsibility.

TECHNICAL DATA

Series	inox line
Min. working pressure	-0.98 bar
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Max. medium temperature	150 °C
Min. operating temperature	-20 °C
Max. operating temperature	150 °C

Material	stainless steel 1.4404
Sealant	FKM, FPM
Medium	compressed air,corrosive media (if compatible with material)
Recommended pipe materials	PVDF, PTFE, PA, PU
Applications	compressed air syst.,chemical and food, pharma, pack.,vacuum
Thread	R 1/4 ET
for tube O.D.	10 mm
L1	24.3 mm
L2	23.0 mm
a/f	16 mm

STANDARDS AND ORIGIN

- Standard thread: ISO 7-1
- Customs tariff number: 73072910
- Country of origin: IN

ABOUT MALE ELBOWS

Push-in L-fittings turn a tube line through 90 degrees and remove the need for a separate elbow ahead of the consumer. The range accepts tube outside diameters from 3 to 16 mm and works up to 10 to 20 bar depending on version. The lower limit goes down to -0.99 bar, so vacuum lines can be built with the same parts.

WHAT MATTERS WHEN CHOOSING

- Thread: The range covers G 1/8 to G 1/2 male, tapered R 1/8 to R 1/2 male, metric M3, M5 and M6 male plus G 1/4 female. Versions with two ports list thread 1 from G 1/8 to G 1/2 female and thread 2 from G 1/8 male to R 1/2 male separately.
- For tube O.D.: The figure of 3 to 16 mm refers to the outside diameter of the tube, not to the nominal bore. It has to match the tube exactly, otherwise the collet loses its grip.
- Working pressure: The upper limit sits between 10 and 20 bar, the lower limit between -0.99 and 0 bar. Vacuum work calls for the version with the negative lower limit.
- Material and sealant: Plastic with nickel-plated brass, all nickel-plated brass and stainless steel 1.4404 are available, sealed with NBR, FKM or FPM, or FKM or FPM in an FDA-compliant version.
- Medium and series: Besides compressed air, the data covers water, neutral gases and liquids, oil and grease as well as corrosive media within the limits of material compatibility. Series range from Blue Series and Blue Series mini through click-clock, metallica and universal short to inox line and NonPlusUltra.

TYPICAL APPLICATIONS

- Connecting pneumatic cylinders where a straight outlet leaves no room at the end cap.
- Piping valve manifolds and control blocks with tight bend radii.
- Vacuum lines on suction cups and handling equipment.

- Plants with wash-down cycles, where stainless steel 1.4404 faces splash water and cleaning agents.
- Filling and packaging lines that need an FDA-compliant seal close to the product.

Thread standards ISO 7-1, DIN EN ISO 228-1 and DIN 13-1 are recorded for part of the 445 items. Operating temperature is given as -20 °C at the low end and, depending on material, 80 to 150 °C at the top.