

Distributor »FUTURA«, Size 2, G 1/2, Pressure switch 0.5 - 10 bar - Riegler 139306

Item no. RGL-139306

Manufacturer Riegler

EAN 4047322531054

Distributor »FUTURA«, Size 2, G 1/2, Pressure switch 0.5 - 10 bar

TECHNICAL DATA

Certification	DIN 40050
Country of Manufacture	Poland
Flow rate [l/min]	7250
Housing material	PA66 GF60
Inlet pressure max. [bar]	16
Material	PA66 GF60
Medium	Compressed air, neutral gases
Pneumatic connection	G1/2
Series	FUTURA
Size BG	2
Thread	G 1/2
Weight	0.48 kg
Zolltarifnummer	84818099



STANDARDS & COMPLIANCE

DIN 40050

DESCRIPTION

Distributor »FUTURA«, Size 2, G 1/2, with mechanical pressure switch, Adjustment range 0.5 - 10 bar, Input pressure max. 16 bar

TECHNICAL DATA

Thread	G 1/2
Size	2
Max. input pressure	16 bar
Min. temperature range	-10 °C
Max. temperature range	50 °C
Housing	PA66 GF60
Adjustment range min.	0.5 bar
Adjustment range max.	10 bar
Connecting thread	material die-cast zinc

A1-ESD equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

fluidics-equipment.com

Page 1/2

Flow rate	7250 l/min
Outlet	2 x G 3/8, 1 x G 1/2
A	63.0 mm
B	150.5 mm
C	113.0 mm
Series	FUTURA
Medium	compressed air, neutral gases
Flow rate measurement	at P1 = 6 bar and pressure drop $\Delta p = 1$ bar

STANDARDS AND ORIGIN

- Customs tariff number: 84818099
- Country of origin: PL

ABOUT SYSTEM EXTENSIONS

System extensions add functions to an existing air preparation unit that filters and regulators do not cover, for example an electrically actuated switching valve that turns plant sections on and off and exhausts them when switched off. The 233 items cover threads from G 1/8 to G 1 and run on an inlet pressure of 9 to 16 bar maximum.

WHAT MATTERS WHEN CHOOSING

- Frame size and thread have to match the existing unit. The range documents G 1/8 to G 1 plus size designations from 0 to 600.
- The series decides whether a module can be added to the assembly. Available lines include FUTURA and FUTURA-mini, SYNTESI, multifix and multifix-mini, variobloc as well as G, G-mini and GA-mini. A module only fits the line it was designed for.
- Choose flow rate from the air demand of the installation rather than from the thread alone. Documented values run from 1400 to 18000 l/min.
- Compare the maximum inlet pressure of 9 to 16 bar against your line pressure. Individual modules are rated for an operating pressure of up to 25 bar.
- Select the housing to suit the environment and the mechanical load. Documented materials are PA66 GF60 and technopolymer, die-cast aluminium and zinc, aluminium and nickel-plated brass.

TYPICAL APPLICATIONS

- Switching plant sections on and off from an electrical signal, with simultaneous exhaust
- Extending existing air preparation units in compressed air distribution
- Making machines pressure-free while they are at standstill
- Distribution points on production lines with several consumers
- Installations that carry neutral gases alongside compressed air

Documented data include protection class IP 65 or IP 65 (P 54) to DIN 40050, NBR seals and medium temperatures from -10 °C to 60 or 70 °C depending on the module. Production takes place in Germany, Italy, Poland and China.

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com