

Captive plug-in connector I.D. 6, ISO 6150 C, Sleeve I.D. 6, red - Riegler 141902

Item no. RGL-141902

Manufacturer Riegler

EAN 4047322566278

Captive plug-in connector I.D. 6, ISO 6150 C, Sleeve I.D. 6, red

TECHNICAL DATA

Colour	Red
Country of Manufacture	Turkey
Length [mm]	100,0
Norm	ISO 6150
Weight	0.087 kg
Zolltarifnummer	84813091



STANDARDS & COMPLIANCE

ISO 6150

DESCRIPTION

Captive plug-in connector I.D. 6, ISO 6150 C, with check valve, 2-stage, Sleeve I.D. 6, red, max. 25 bar, Temp. -15°C to 200°C

TECHNICAL DATA

Colour	red
Length	100.0 mm

STANDARDS AND ORIGIN

- Customs tariff number: 84813091
- Country of origin: TR

ABOUT STEMS AND PLUGS

Hose barbs and nipples create the releasable link between the compressed air line, the hose and the tool. The group covers connection threads from G 1/8 to G 1/2 plus tapered R threads and NPT 3/8 male. Overall lengths run from 17 to 145 mm, which often decides whether a part fits a tight connection point.

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

WHAT MATTERS WHEN CHOOSING

- Connection: Start by settling male or female thread. G 1/8, G 1/4, G 3/8 and G 1/2 are available in both, together with tapered R 1/4, R 3/8 and R 1/2 male and NPT 3/8 male for US-style fittings.
- Length: Overall length ranges from 17 to 145 mm and follows the design of the part. It becomes a hard limit behind wall fittings or in panel cut-outs where space is short.
- Material: Nickel-plated brass and nickel-plated steel are documented. Steel is the choice where frequent coupling and hose pull define the mechanical load.
- Max. operating pressure: Parts with a stated pressure figure are rated at 15 bar. Check that value against line pressure and against pressure peaks in the tool circuit before the barb is crimped.

TYPICAL APPLICATIONS

- Connecting pneumatic tools to workshop hoses through quick couplings.
- Fixed take-off points on ring mains, with the nipple screwed into the wall fitting.
- Assembling hose lines between the air preparation unit and the consumer.
- Assembly stations with changing tools where the connection is opened several times a day.
- Vibration-damping intermediate sections with PVC hose ahead of pulsating tools.

The documented materials are nickel-plated brass and nickel-plated steel. The 482 items in this group come from production in Germany, Italy, Sweden, Greece, Turkey, the USA and China.