

Filter regulator »FUTURA«, PC, Size 2, G 3/8, 0.2-4 bar, Fully a. - Riegler 151796

Item no. RGL-151796

Manufacturer Riegler

EAN 4047322595599

Filter regulator »FUTURA«, PC, Size 2, G 3/8, 0.2-4 bar, Fully a.

TECHNICAL DATA

Condensate drain	fully automatic
Control range max. [bar]	4
Country of Manufacture	Germany
Filter grade [µm]	5
Flow rate [l/min]	4500
Housing material	PA66 GF60
Inlet pressure max. [bar]	16
Material	PA66 GF60
Medium	Compressed air, neutral gases
Pneumatic connection	G3/8
Seal material	NBR
Series	FUTURA
Size BG	2
Thread	G 3/8
Weight	0.868 kg
Zolltarifnummer	84811005



DESCRIPTION

Filter regulator »FUTURA«, with PC container, Protective cage, Pressure gauge, 5 µm, Size 2, G 3/8, Control range 0.2-4 bar, Fully Filter regulators with excellent flow rates in modern design. The regulator knob can be latched and locked.

TECHNICAL DATA

Thread	G 3/8
Size	2
Min. input pressure	1.5 bar
Max. input pressure	16 bar
Min. temperature range	-10 °C
Max. temperature range	50 °C
Housing	PA66 GF60
Connecting thread	material die-cast zinc
Sealant	NBR

Diaphragms	NBR
Filter element	cellpor (PE)
Filter rating	5 µm
Flow rate	4500 l/min
Condensate drain	fully-automatic
Min. control range	0.2 bar
Max. control range	4 bar
Pressure gauge display min.	0 bar
Pressure gauge display max.	6 bar
Bowl	polycarbonate container with protective cage
A	63.0 mm
B	273.0 mm
C	110.0 mm
Series	FUTURA
Medium	compressed air, neutral gases
Flow rate measurement	at P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar

STANDARDS AND ORIGIN

- Customs tariff number: 84811005
- Country of origin: DE

ABOUT FILTER REGULATORS

A filter regulator combines particle separation and pressure control in one body, which saves a connection point in the air preparation unit. The range filters at 5 to 50 µm and regulates to outlet pressures between 1 and 17.5 bar. Permissible inlet pressure runs from 10 to 60 bar depending on version.

WHAT MATTERS WHEN CHOOSING

- Thread and DN: Ports run from G 1/8 to G 1, nominal bores from 5 to 25 mm. Thread size alone is not enough as a criterion, because only the nominal bore describes the actual flow cross section.
- Filter rating: 5 to 50 µm. The coarse end is enough for general tool and cylinder supply, finer elements protect sensitive valve technology and trade that against a higher pressure drop.
- Control range and inlet pressure: Lower limits lie between 0 and 1.7 bar, upper limits between 1 and 17.5 bar. The target working pressure should sit inside the range rather than at its edge, and the inlet pressure of 10 to 60 bar has to match the supply.
- Flow rate: Listed values run from 1000 to 15000 l/min. What counts is the peak demand of all downstream consumers, not their average.
- Condensate drain: Manual drain, hand drain valve, semi-automatic and fully automatic versions are available, including a normally closed type. Where the unit sits in a poorly accessible spot, the fully automatic drain is the practical option.

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 2/3

TYPICAL APPLICATIONS

- Central air preparation unit ahead of valve manifolds and cylinders on a machine.
- Supply for pneumatic tools at assembly and workshop stations.
- Packaging and filling lines with fluctuating air demand.
- Paint and coating equipment that requires finely filtered, oil-free air.
- Test benches that need a stable outlet pressure independent of line pressure.

Documented sealing materials are NBR, PU with HNBR and FKM. Housing materials include PA66 GF60, technopolymer, zinc and aluminium die casting as well as stainless steel 1.4404 (AISI 316L) and 1.4401 (AISI 316). The 420 items belong to the FUTURA, SYNTESI, multifix, variobloc, GA and Standard series along with their mini sizes.

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 3/3