

Service unit 3-part »FUTURA«, PC, Size 1, G 3/8, 0.2-4, Semi a. - Riegler 152620

Item no. RGL-152620

Manufacturer Riegler

EAN 4047322603607

Service unit 3-part »FUTURA«, PC, Size 1, G 3/8, 0.2-4, Semi a.

TECHNICAL DATA

Condensate drain	semi-automatic
Control range max. [bar]	4
Country of Manufacture	Germany
Filter grade [µm]	5
Flow rate [l/min]	1750
Housing material	PA66 GF60
Inlet pressure max. [bar]	16
Material	PA66 GF60
Medium	Compressed air, neutral gases
Pneumatic connection	G3/8
Seal material	NBR
Series	FUTURA
Size BG	1
Thread	G 3/8
Weight	1.55 kg
Zolltarifnummer	84811005



DESCRIPTION

Service unit 3-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 1, G 3/8, Control range 0.2 - 4 bar, Semi Three-piece service units with excellent flow rates in modern design. Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

TECHNICAL DATA

Thread	G 3/8
Size	1
Min. input pressure	1.5 bar
Max. input pressure	16 bar
Min. temperature range	-10 °C
Max. temperature range	50 °C
Housing	PA66 GF60
Connecting thread	material die-cast zinc

Sealant	NBR
Diaphragms	NBR
Filter element	cellpor (PE)
Filter rating	5 µm
Sight dome	PC
Flow rate	1750 l/min
Condensate drain	semi-automatic
Min. control range	0.2 bar
Max. control range	4 bar
Pressure gauge display min.	0 bar
Pressure gauge display max.	6 bar
Bowl	polycarbonate container with protective cage
A	156.0 mm
B	226.0 mm
C	96.0 mm
Series	FUTURA
Medium	compressed air, neutral gases
Flow rate measurement	at P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar

STANDARDS AND ORIGIN

- Customs tariff number: 84811005
- Country of origin: DE

ABOUT SERVICE SYSTEMS MULTI-PART

Multi-part air preparation units combine filter, regulator and lubricator in one assembly and condition the compressed air right before the machine. The range filters from 5 to 40 µm, regulates to end pressures between 1 and 16 bar and handles flow rates from 300 to 13500 l/min.

WHAT MATTERS WHEN CHOOSING

- Flow rate from 300 to 13500 l/min: size it to the machine's real air demand, otherwise pressure collapses on load peaks.
- Filter rating between 5 and 40 µm: coarser elements last longer, finer ones give valves and cylinders better protection.
- Control range: lower limits fall between 0 and 2.5 bar, upper limits between 1 and 16 bar. Keep the working pressure away from the edge of the range you choose.
- Condensate drain, manual, semi-automatic (RMSA) or fully automatic (RA, also the version closed when depressurised): automatic drains pay off where access is poor or condensate loads are high.
- Port size from G 1/8 to G 1 1/2 and body size BG: both have to suit line size and flow. Maximum inlet pressure runs between 10 and 25 bar depending on version.

TYPICAL APPLICATIONS

- Central conditioning at the air inlet of a machine or cell
- Supply for air tools at assembly workstations
- Lubrication of impact tools and air motors through the lubricator stage
- Preparing control air for valve manifolds and pneumatic controls
- Separate pressure levels for individual sections of a production line

The intended media are compressed air and neutral gases, seals are NBR. Bodies range from technopolymer and PA66 GF60 through zinc die-cast to aluminium die-cast, and the 801 items are spread across the FUTURA, SYNTESI, multifix, variobloc, GA, ONE and Standard series including their mini versions.