

Straight reducer, Pipe exterior Ø 16/12, galvanised steel - Riegler 159340

Item no. RGL-159340


Manufacturer Riegler

EAN 4047322640022

Straight reducer, Pipe exterior Ø 16/12, galvanised steel

TECHNICAL DATA

Country of Manufacture	Italy
Material	Zinc-plated steel (DIN 2353)
Nominal pressure PN [bar]	400
Norm	DIN 2353
Weight	0.185 kg
Zolltarifnummer	73079910



STANDARDS & COMPLIANCE

DIN 2353

DESCRIPTION

Straight reducer, Pipe exterior Ø Female connector 16/12 mm, PN max. 400 bar, a/f1 27, a/f2 30, a/f3 24, galvanised steel Straight reducers, heavy type

TECHNICAL DATA

Material	galvanised steel (DIN 2353)
L1	54.0 mm
a/f 1	27 mm
a/f 2	30 mm
a/f 3	24 mm
PN	400 bar
Female connector Ø	16/12 mm

STANDARDS AND ORIGIN

- Customs tariff number: 73079910
- Country of origin: IT

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

ABOUT REDUCING UNIONS

A reducing coupling joins two cutting ring fittings of different tube size directly, without an additional adapter piece in between. It steps a line down in cross section, for example where a thinner branch runs off a larger main line. The series covers nominal pressures from 160 to 630 bar.

WHAT MATTERS WHEN CHOOSING

- PN: the group runs from 160 to 630 bar, with a large share of the items rated PN max. 315 bar. The rating has to cover the highest pressure in the line, pressure peaks included.
- Socket diameter: the pairing of the two tube outside diameters decides which tubes can be joined, with combinations from 8/6 mm up to 18/12 mm. Both figures have to match the cutting rings already fitted.
- Design: the items in this group are made for the light series. They have to suit the tube and the rest of the fitting system, otherwise the cutting ring will not seal properly.
- Material: all 32 items are galvanised steel to DIN 2353. The material sets corrosion protection and media compatibility and should stay consistent along the whole line.
- Spanner sizes: SW 1, SW 2 and SW 3 grow with the size, with values from 14 to 27. They determine the tool needed for tightening and the clearance required around the fitting.

TYPICAL APPLICATIONS

- Hydraulic lines in machine and plant construction where the tube cross section changes between sections
- Connecting thinner control and gauge lines to a larger supply line
- Rebuilds and repairs where a section is re-run in a different tube diameter
- Hydraulic power units and presses working in the upper bar range
- Mobile hydraulics on commercial vehicles and construction machinery, where adapter stacks cost space and weight

All 32 items are galvanised steel to DIN 2353. Production is in Italy.