

Pressure regulator »GA-mini«, Size 200, G 1/8, 0.5 - 9 bar - Riegler 178353

Item no. RGL-178353

Manufacturer Riegler

EAN 4047322666244

Pressure regulator »GA-mini«, Size 200, G 1/8, 0.5 - 9 bar

TECHNICAL DATA

Control range max. [bar]	9
Country of Manufacture	China
Flow rate [l/min]	1400
Housing material	Die-cast aluminium
Inlet pressure max. [bar]	10
Material	Die-cast aluminium
Pneumatic connection	G1/8
Seal material	NBR
Series	GA-mini
Size BG	200
Thread	G 1/8
Weight	0.243 kg
Zolltarifnummer	84811099



DESCRIPTION

Pressure regulator »GA-mini« pressure gauge, Mounting bracket, Size 200, G1/8, Input pressure max. 10 bar, Control range 0.5-9 bar Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure setting can be locked by pushing the button down.

TECHNICAL DATA

Thread	G 1/8
Size	200
Max. input pressure	10 bar
Housing	die-cast aluminium
Sealant	NBR
Spring bonnet	POM
Min. control range	0.5 bar
Max. control range	9 bar
Flow rate	1400 l/min
A	52.5 mm
B	91.0 mm

C	65.5 mm
D	25.5 mm
Series	GA-mini

Flow rate measurement at P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

STANDARDS AND ORIGIN

- Customs tariff number: 84811099
- Country of origin: CN

ABOUT PRESSURE REGULATORS

Pressure regulators hold the outlet pressure steady even when inlet pressure varies or consumption changes. The range covers control ranges starting between 0 and 5 bar and ending between 1 and 200 bar, with inlet pressures up to 60 bar. Ports run from G 1/8 to G 2.

WHAT MATTERS WHEN CHOOSING

- Control range: lower limits sit between 0 and 5 bar, upper limits between 1 and 200 bar. Keep the working pressure inside the range rather than at its edge.
- Flow rate from 1000 to 50000 l/min: the regulator has to cover peak demand, otherwise secondary pressure drops away on every load peak.
- Medium: besides compressed air and neutral gases there are versions for drinking water, nitrogen and argon, plus variants for ultra-fine filtered oil-free air down to 0.01 μm .
- Body material: aluminium, aluminium die-cast, brass, zinc die-cast, technopolymer, PA66 GF60, stainless steel 1.4404 (AISI 316L) and gunmetal in the Rg5, CC499K and 2.1096.01 grades.
- Series: alongside the mechanical FUTURA, SYNTESI, multifix, variobloc, inline and Standard lines, the electronically controlled REGTRONIC 300 and 400 series handle setpoint-driven applications.

TYPICAL APPLICATIONS

- Holding a steady working pressure at machines and air tools
- Reducing mains pressure to the level required by individual sub-circuits
- Setpoint-driven pressure control on test rigs using the electronic versions
- Pressure reduction in drinking water lines
- Feeding test and measuring rigs with nitrogen or argon

Sealing materials include NBR, FKM, FPM, EPDM, SBR, PU, HNBR and TPU depending on the series. 102 items are rated to protection class IP 65.