

Filter regulator »GA-mini«, 5 µm, Size 200, G 1/8, 1.5 - 9 bar - Riegler 178357

Item no. RGL-178357

Manufacturer Riegler

EAN 4047322666282

Filter regulator »GA-mini«, 5 µm, Size 200, G 1/8, 1.5 - 9 bar

TECHNICAL DATA

Condensate drain	semi-automatic
Control range max. [bar]	9
Country of Manufacture	China
Filter grade [µm]	5
Flow rate [l/min]	1050
Housing material	Die-cast aluminium
Inlet pressure max. [bar]	10
Material	Die-cast aluminium
Pneumatic connection	G1/8
Seal material	NBR
Series	GA-mini
Size BG	200
Thread	G 1/8
Weight	0.32 kg
Zolltarifnummer	84811005



DESCRIPTION

Filter regulator »GA-mini« PC container, Mounting bracket, 5 µm, Size 200, G1/8, Input press. max. 10 bar, Control range 1.5-9 bar Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the button down.

TECHNICAL DATA

Thread	G 1/8
Size	200
Max. input pressure	10 bar
Housing	die-cast aluminium
Sealant	NBR
Filter rating	5 µm
Spring bonnet	POM
Min. control range	1.5 bar
Max. control range	9 bar

Bowl	polycarbonate container
Flow rate	1050 l/min
Condensate drain	semi-automatic
A	52.5 mm
B	171.0 mm
C	73.0 mm
D	98.0 mm
Series	GA-mini
Flow rate measurement	at P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

STANDARDS AND ORIGIN

- Customs tariff number: 84811005
- Country of origin: CN

ABOUT FILTER REGULATORS

A filter regulator combines particle separation and pressure control in one body, which saves a connection point in the air preparation unit. The range filters at 5 to 50 μm and regulates to outlet pressures between 1 and 17.5 bar. Permissible inlet pressure runs from 10 to 60 bar depending on version.

WHAT MATTERS WHEN CHOOSING

- Thread and DN: Ports run from G 1/8 to G 1, nominal bores from 5 to 25 mm. Thread size alone is not enough as a criterion, because only the nominal bore describes the actual flow cross section.
- Filter rating: 5 to 50 μm . The coarse end is enough for general tool and cylinder supply, finer elements protect sensitive valve technology and trade that against a higher pressure drop.
- Control range and inlet pressure: Lower limits lie between 0 and 1.7 bar, upper limits between 1 and 17.5 bar. The target working pressure should sit inside the range rather than at its edge, and the inlet pressure of 10 to 60 bar has to match the supply.
- Flow rate: Listed values run from 1000 to 15000 l/min. What counts is the peak demand of all downstream consumers, not their average.
- Condensate drain: Manual drain, hand drain valve, semi-automatic and fully automatic versions are available, including a normally closed type. Where the unit sits in a poorly accessible spot, the fully automatic drain is the practical option.

TYPICAL APPLICATIONS

- Central air preparation unit ahead of valve manifolds and cylinders on a machine.
- Supply for pneumatic tools at assembly and workshop stations.
- Packaging and filling lines with fluctuating air demand.
- Paint and coating equipment that requires finely filtered, oil-free air.
- Test benches that need a stable outlet pressure independent of line pressure.

Documented sealing materials are NBR, PU with HNBR and FKM. Housing materials include PA66

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 2/3

GF60, technopolymer, zinc and aluminium die casting as well as stainless steel 1.4404 (AISI 316L) and 1.4401 (AISI 316). The 420 items belong to the FUTURA, SYNTESI, multifix, variobloc, GA and Standard series along with their mini sizes.

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 3/3