

Service unit 2-part »GA-mini«, 5 µm, Size 200, G 1/4, 1.5 - 9 bar - Riegler 178362

Item no. RGL-178362

Manufacturer Riegler

EAN 4047322666336

Service unit 2-part »GA-mini«, 5 µm, Size 200, G 1/4, 1.5 - 9 bar

TECHNICAL DATA

Condensate drain	semi-automatic
Control range max. [bar]	9
Country of Manufacture	China
Filter grade [µm]	5
Flow rate [l/min]	900
Housing material	Die-cast aluminium
Inlet pressure max. [bar]	10
Material	Die-cast aluminium
Pneumatic connection	G1/4
Seal material	NBR
Series	GA-mini
Size BG	200
Thread	G 1/4
Weight	0.553 kg
Zolltarifnummer	84811005



DESCRIPTION

Service unit 2-part »GA-mini«, with PC container, 5 µm, Size 200, G 1/4, Input pressure max. 10 bar, Control range 1.5 - 9 bar Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

TECHNICAL DATA

Thread	G 1/4
Size	200
Max. input pressure	10 bar
Housing	die-cast aluminium
Sealant	NBR
Filter rating	5 µm
Sight dome	brass/POM
Spring bonnet	POM
Min. control range	1.5 bar

Max. control range	9 bar
Flow rate	900 l/min
Condensate drain	semi-automatic
A	108.0 mm
B	171.0 mm
C	73.0 mm
D	98.0 mm
Series	GA-mini
Flow rate measurement	at P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

STANDARDS AND ORIGIN

- Customs tariff number: 84811005
- Country of origin: CN

ABOUT SERVICE SYSTEMS MULTI-PART

Multi-part air preparation units combine filter, regulator and lubricator in one assembly and condition the compressed air right before the machine. The range filters from 5 to 40 μm , regulates to end pressures between 1 and 16 bar and handles flow rates from 300 to 13500 l/min.

WHAT MATTERS WHEN CHOOSING

- Flow rate from 300 to 13500 l/min: size it to the machine's real air demand, otherwise pressure collapses on load peaks.
- Filter rating between 5 and 40 μm : coarser elements last longer, finer ones give valves and cylinders better protection.
- Control range: lower limits fall between 0 and 2.5 bar, upper limits between 1 and 16 bar. Keep the working pressure away from the edge of the range you choose.
- Condensate drain, manual, semi-automatic (RMSA) or fully automatic (RA, also the version closed when depressurised): automatic drains pay off where access is poor or condensate loads are high.
- Port size from G 1/8 to G 1 1/2 and body size BG: both have to suit line size and flow. Maximum inlet pressure runs between 10 and 25 bar depending on version.

TYPICAL APPLICATIONS

- Central conditioning at the air inlet of a machine or cell
- Supply for air tools at assembly workstations
- Lubrication of impact tools and air motors through the lubricator stage
- Preparing control air for valve manifolds and pneumatic controls
- Separate pressure levels for individual sections of a production line

The intended media are compressed air and neutral gases, seals are NBR. Bodies range from technopolymer and PA66 GF60 through zinc die-cast to aluminium die-cast, and the 801 items are spread across the FUTURA, SYNTESI, multifix, variobloc, GA, ONE and Standard series including their mini versions.