

Guide unit for ISO15552-Ø 40mm, stroke 160mm

Item no. FL-033013

Manufacturer Fluidics equipment

EAN 4050571465018

Guide unit for ISO15552-Ø 40mm, stroke 160mm

TECHNICAL DATA

Norm	ISO 15552
Weight	2.7 kg
Zolltarifnummer	84123100



STANDARDS & COMPLIANCE

ISO15552

DESCRIPTION

Function:

Guide units are used for anti-rotation safety and absorbing side forces with standard cylinders.

Materials:

Body: anodized aluminium, guide rods: hard chromium plated steel, wiper: NBR, bearing: steel or sintered bronze

Temperature range:

-30 to +100 °C

Version	H with ball guide
for piston diameter [mm]	40
Stroke [mm]	160
MA / MB* [Nm]	29 / 16
A [mm]	115
B [mm]	58

A1-ESD equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

fluidics-equipment.com

Page 1/2

C [mm]	58,2
CH [mm]	15
D [mm]	28
E [mm]	11,0
F [mm]	112
G [mm]	55
H [mm]	12
I [mm]	16
L1 [mm]	207
L2 [mm]	15
L3 [mm]	80
L4 [mm]	140
N [mm]	6,6
O [mm]	12
P [mm]	11
Q [mm]	6,5
S	M 6
T [mm]	84
U [mm]	69
V [mm]	38,0
Z [mm]	87