

Bellows suction pad, 2,5-way, Ø 9x2mm, NBR (55A), black

Item no. FL-550700

Manufacturer Fluidics equipment

EAN 4050571889777

Bellows suction pad, 2,5-way, Ø 9x2mm, NBR (55A), black

TECHNICAL DATA

Weight	0.0007 kg
Zolltarifnummer	84879090

**DESCRIPTION****CR material:**

Description: Chloroprene; temperature range: -40°C up to max. +110°C; wear resistant: fair; resistance to oil: good; Weather and ozone resistance: good; petrol resistance: not recommended; advantage weather resistant; Recommended for: Universal use

NBR material:

Description: Nitrile rubber; temperature range: -30°C up to max. +90°C; wear resistant: fair; resistance to oil: very good; Weather and ozone resistance: not recommended; petrol resistance: fair; Advantage: oil-resistant, water-resistant up to max. 70°C; recommendation for: Universal use

Material silicone:

Description: Silicone rubber; Temperature range: -40°C up to max. +200°C; wear resistant: not recommended; oil resistance: not recommended; Weather and ozone resistance: very good; petrol resistance: not recommended; advantage Temperature resistant, very flexible; Recommended for: Food, electronics

PUR material:

Description: Polyurethane; Temperature range: -20°C up to max. +80°C; wear resistant: good; oil resistance: very good; Weather and ozone resistance: fair; petrol resistance: good; advantage: long service life; recommended for: harsh operating conditions, automobile

NR material:**A1-ESD equipment**

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

Description: Natural rubber; temperature range. -40°C up to max. +80°C; wear resistant: good; oil resistance: not recommended; Weather and ozone resistance: not recommended; petrol resistance: not recommended; advantage flexible, wear-resistant; recommended for: Wood, uneven surfaces

NRE material:

Description: Natural rubber; temperature range. -40°C up to max. +80°C; wear resistant: good; oil resistance: not recommended; Weather and ozone resistance: not recommended; petrol resistance: not recommended; advantage very flexible, wear-resistant; recommended for: Wood, uneven surfaces

SBR material:

Description: Styrene-butadiene rubber; temperature range: -30°C up to max. +80°C; wear resistant: very good; oil resistance: not recommended; Weather and ozone resistance: fair; petrol resistance: fair; Advantage: non-marking, very flexible, very abrasion resistant; recommended for: Wood, uneven surfaces

Scope of delivery:

1 pc Suction cup (bracket must be ordered separately)

Material	NBR (55A)
D [mm]	Ø 9
Stroke [mm]	2
colour	black
Connection (female thread)	G 1/8"
Holder (female thread)	VSH F18 I
Connection (male thread)	G 1/8"
Holder (male thread)	VSH F18
D1 [mm]	5
D2 [mm]	9
D3 [mm]	4
h [mm]	15
H [mm]	27,5
Temperature range [°C]	-30 to +90
Bracket type	F

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com