

Short-stroke cylinders, double acting, piston 32 mm, stroke 5 mm

Item no. FL-248725

Manufacturer Fluidics equipment

EAN 4050571523183

Short-stroke cylinders, double acting, piston 32 mm, stroke 5 mm

TECHNICAL DATA

Weight 0.155 kg

Zolltarifnummer 84799070



DESCRIPTION

Materials:

Head and base plate: Anodised aluminium / brass, cylinder tube: Anodised aluminium, piston rod: 1.4305 seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Cylinder switch type:

G

Piston diameter [mm]	32
Stroke [mm]	5
Version	without magnetic piston
C1 (piston rod thread)	M 6
P (compressed air port)	G 1/8"
A [mm]	51,0
B [mm]	46

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

D [mm]	12
F [mm]	5,8
G [mm]	9,0
H [mm]	27,0
I [mm]	32
J [mm]	11,5
K [mm]	36,0
L [mm]	29,5
N [mm]	34,0
Q [mm]	5,7
S [mm]	48,0
T [mm]	12
V [mm]	10
W [mm]	6,0
X [mm]	28
Y [mm]	17
Z [mm]	20
AA [mm]	11,0
AB [mm]	10