

# Short stroke cylinder, non-rotating, 63, stroke 20mm

**Item no.** FL-247697 **Manufacturer** Fluidics equipment

**Manufacturer no.** NDM 63/20 A **EAN** 4050571524838

Short stroke cylinder, non-rotating, 63, stroke 20mm

## TECHNICAL DATA



Artikel-Authentizität **Originalprodukt**

Artikelzustand **Neu**

Weight **85 kg**

Zolltarifnummer **84799070**

## DESCRIPTION

Materials:

Head and base plate: Anodised aluminium / brass, cylinder tube: Anodised aluminium, piston rod: 1.4305 seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

G

Piston diameter [mm] 63

Stroke [mm] 20

P (compressed air port) G 1/8"

A [mm] 89,0

B [mm] 80

C2 M 6

### A1-ESD equipment

Keldersstr. 15  
42697 Solingen, Deutschland  
VAT ID: DE269659389

Phone: +49 212 38340680  
shop@esd-equipment.com  
**fluidics-equipment.com**

D [mm]	16
E [mm]	38,5
F [mm]	9,0
G [mm]	14,0
H [mm]	46,0
I [mm]	62
J [mm]	11,0
K [mm]	62
L [mm]	42,0
N [mm]	60,0
Q [mm]	8,8
S [mm]	80,0
T [mm]	14
U [mm]	8,0
V [mm]	13
W [mm]	7,0
X [mm]	50
Y [mm]	22
Z [mm]	30
AA [mm]	15,0
AB [mm]	12