

ISO 15552 cylinders, piston 250 mm, stroke 1500 mm, ECO

Item no. FL-273709

Manufacturer Fluidics equipment

EAN 4050571699024

ISO 15552 cylinders, piston 250 mm, stroke 1500 mm, ECO

TECHNICAL DATA

Norm	ISO 15552
Weight	1 kg
Zolltarifnummer	84799070



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium section tube, Piston rod: Steel, hard chrome-plated, piston: Aluminium, Gasket: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A, Ø 125 and larger: C in combination with fastening C1 or C in combination with fastening C2

Piston diameter [mm]	250
Stroke [mm]	1500

A1-ESD equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

fluidics-equipment.com

Page 1/2

A (piston rod thread)	M 42x2
G (compressed air port)	G 1"
B [mm]	50
C [mm]	90
D [mm]	75
F [mm]	84
G [mm]	105
H [mm]	305
K [mm]	8,0
M [mm]	270,0
N [mm]	220,0
CH [mm]	46
RT	M 20