

Guide unit for ISO15552-Ø 63mm, stroke 100mm

Item no. FL-250487

Manufacturer Fluidics equipment

EAN 4050571465537

Guide unit for ISO15552-Ø 63mm, stroke 100mm

TECHNICAL DATA

Norm	ISO 15552
Weight	3.6 kg
Zolltarifnummer	84123100



STANDARDS & COMPLIANCE

ISO15552

DESCRIPTION

Function:

Guide units are used for anti-rotation safety and absorbing side forces with standard cylinders.

Materials:

Body: anodized aluminium, guide rods: hard chromium plated steel, wiper: NBR, bearing: steel or sintered bronze

Temperature range:

-30 to +100 °C

Version	C with sliding guide
for piston diameter [mm]	63
Stroke [mm]	100
MA / MB* [Nm]	26 / 23
A [mm]	152
B [mm]	85

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

C [mm]	85,2
CH [mm]	20
D1 [mm]	25
E1 [mm]	15,30
E2 [mm]	56,5
E3 [mm]	15,30
F [mm]	147
G [mm]	80
H [mm]	15
I [mm]	20
L6 [mm]	161
L7 [mm]	64
L8 [mm]	76
N [mm]	9,0
O [mm]	16
P [mm]	15
Q [mm]	9,0
S	M 8
T [mm]	105
U [mm]	100
V [mm]	56,5
Z [mm]	119