

6WV38-12V. 6/2-way hydraulic valve, G 3/8", 12V DC

Item no. FL-6WV38-12V

Manufacturer Fluidics equipment

EAN 4050571208691

6/2-way hydraulic valve, G 3/8", 12 V DC

TECHNICAL DATA

Weight	3.3 kg
Zolltarifnummer	84812010

**DESCRIPTION**

Suitable:

6/2-way valves are electrical, direct actuating gate valves for inline assembly. With this, 2 consumers can be alternating supplied by one source. These valves are frequently used if for example only one control device is available but an additional function is required.

Materials:

Body: Spheroidal cast iron, internal parts: Steel, seals: NBR

Temperature range:

-20°C to +80°C (environment: -20°C to +50°C)

Media:

Hydraulic oils on the basis of mineral oil

Control voltages:

24 V DC, 12 V DC

Voltage tolerance:

± 10 %

Protection class:

IP 65 (plug size 3)

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

Operating pressure:
0 to 250 bar

Pressure input:
Possible on every connection

Information:
These valves are always supplied with a solenoid coil and a connector plug.