

Serie AV05 R422103077 AV05-5/2AS-VT00-024VDC-NO - Aventics 5/2-Wegeventil

Item no. AVE-R422103077

Manufacturer Aventics

Serie AV05 R422103077 AV05-5/2AS-VT00-024VDC-NO. Aventics pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Country of Manufacture	Germany
Weight	0.07 kg
Zolltarifnummer	84812090



DESCRIPTION

Aventics pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Actuation	elektrisch
NennFlow Qn	700 l/min
Schaltprinzip	5/2
BetriebsPressure min.	-0.9 bar
BetriebsPressure max.	10 bar
BetriebsVoltage DC	24 V
Voltagestoleranz DC	-10% / +10%
HandhilfsActuation	ohne
Actuationsfunktion	einseitig betätigt
Dichtprinzip	weich dichtend
Vorsteuerung	extern
Design Ventil	Schieberventil, überschneidungsfrei

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Portart	Plattenanschluss
Rückstellung	mit Feder-/Luftfederrückstellung
Verblockungsprinzip	Grundplattenprinzip mehrfach
SteuerPressure min.	3 bar
SteuerPressure max.	8 bar
UmgebungsTemperature min.	-10 °C
UmgebungsTemperature max.	60 °C
MediumsTemperature min.	-10 °C
MediumsTemperature max.	60 °C
Medium	Druckluft
Max. Partikelgröße	40 µm
Ölgehalt der Pressureluft min.	0 mg/m ³
Ölgehalt der Pressureluft max.	5 mg/m ³

VERSION

Serie AV05 R422103077 AV05-5/2AS-VT00-024VDC-NO.

MANUFACTURER

Genuine Aventics.