

Serie CD07 R432016608 CD07-DS-DBL-EXT-PLT - Aventics 5/2-Wegeventil

Item no. AVE-R432016608

Manufacturer Aventics

Serie CD07 R432016608 CD07-DS-DBL-EXT-PLT. Aventics pneumatic valve controls direction and flow of compressed air quickly and reliably for dynamic automation.

TECHNICAL DATA

Country of Manufacture	Germany
Norm	EN 175301-803
Weight	0.75 kg
Zolltarifnummer	84812090



DESCRIPTION

Aventics pneumatic valve controls direction and flow of compressed air quickly and reliably for dynamic automation.

TECHNICAL DATA

Actuation	elektrisch
Baugröße	CD07 - inch
Schaltprinzip	5/2, beidseitig betätigt
Actuationsfunktion	beidseitig betätigt
HandhilfsActuation	rastend
Vorsteuerung	extern
NennFlow Qn	1200 l/min
DruckluftPort	1/4 NPT
BetriebsPressure min.	2 bar
BetriebsPressure max.	10 bar
BetriebsVoltage	230 V AC
Elektrischer Port Typ	Stecker

Elektrischer Port Größe	EN 175301-803, Form A
Norm elektr. Port	EN 175301-803:2006
Schutzart mit Port	IP65
Verpolungsschutz	verpolungssicher
Kompatibilitätsindex	13, 14
Einschaltdauer	100 %
typ. Einschaltzeit	21 ms
typ. Ausschaltzeit	21 ms
Dichtprinzip	weich dichtend
UmgebungsTemperature min.	-15 °C
UmgebungsTemperature max.	50 °C
Weight	0.75 kg
Housing material	Zink-Druckguss, Polyamid glasfaserverstärkt

VERSION

Serie CD07 R432016608 CD07-DS-DBL-EXT-PLT.

MANUFACTURER

Genuine Aventics.