

Serie ES05 R422103178 ES05-2X3/200-D8-24VDC-SGL - Aventics 2x3/2-Wegeventil

Item no. AVE-R422103178

Manufacturer Aventics

Serie ES05 R422103178 ES05-2X3/200-D8-24VDC-SGL. Aventics pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Country of Manufacture **Germany**

Weight **0.1 kg**

Zolltarifnummer **84812090**

Kein Produktbild

DESCRIPTION

Aventics pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Actuation	elektrisch
NennFlow Qn	370 l/min
Schaltprinzip	2x3/2
Ausführung	NO/NO
DruckluftPort Ausgang	Ø 8
BetriebsPressure min.	3 bar
BetriebsPressure max.	8 bar
BetriebsVoltage DC	24 V
Voltagestoleranz DC	-15% / +10%
HandhilfsActuation	nicht rastend
Elektrischer Port Größe	Form C Industrie
Actuationsfunktion	einseitig betätigt
Zertifikate	UR (Underwriters Laboratories)

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

UmgebungsTemperature min.	5 °C
UmgebungsTemperature max.	50 °C
MediumsTemperature min.	5 °C
MediumsTemperature max.	50 °C
Medium	Druckluft
Max. Partikelgröße	40 µm
Ölgehalt der Pressureluft min.	0 mg/m³
Ölgehalt der Pressureluft max.	5 mg/m³
DruckluftPort Eingang	Ø 8
DruckluftPort Entlüftung	Ø 8
Leistungsaufnahme DC	2 W
Einschaltdauer	100 %

VERSION

Serie ES05 R422103178 ES05-2X3/200-D8-24VDC-SGL.

MANUFACTURER

Genuine Aventics.