

24° Weld Cone with O-Ring for 38x5 mm Rohre with O-Ring Steel, phosphated - Stauff 6020000194

Item no. STF-6020000194

Manufacturer Stauff

24° Weld Cone with O-Ring for 38x5 mm Rohre with O-Ring Steel, phosphated. The STAUFF tube fitting connects hydraulic tubes tightly and detachably on the 24° cutting-ring principle to DIN 2353 / EN ISO 8434-1.

TECHNICAL DATA

Country of Manufacture	Germany
Material	Steel
Weight	0.24 kg
Zolltarifnummer	73079319



STANDARDS & COMPLIANCE

ISO 8434-1 DIN 2353

DESCRIPTION

The STAUFF tube fitting connects hydraulic tubes tightly and detachably on the 24° cutting-ring principle to DIN 2353 / EN ISO 8434-1. On tightening, the cutting ring bites into the tube and creates a positive, force-fit, metal-sealing joint.

BENEFITS

- Reliable 24° cutting-ring joint to DIN 2353 / EN ISO 8434-1
- Detachable and reusable with consistent tightness
- Zinc/nickel or stainless steel surfaces for high corrosion protection

VERSION

24° Weld Cone with O-Ring for 38x5 mm Rohre with O-Ring Steel, phosphated.

APPLICATIONS

Connection of hydraulic tubes in power units, machines and plant at high working pressures.

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/1