

Vormontagegestutzen 12S for SPR-PRC-H-M - Stauff 6030013222

Item no. STF-6030013222

Manufacturer Stauff

Vormontagegestutzen 12S for SPR-PRC-H-M. The STAUFF tube fitting connects hydraulic tubes tightly and detachably on the 24° cutting-ring principle to DIN 2353 / EN ISO 8434-1.

TECHNICAL DATA

Country of Manufacture **Germany**Norm **DIN 2353, EN ISO 8434-1**Weight **0.148 kg**Zolltarifnummer **82073010**

STANDARDS & COMPLIANCE

ISO 8434-1 **DIN 2353**

DESCRIPTION

The STAUFF tube fitting connects hydraulic tubes tightly and detachably on the 24° cutting-ring principle to DIN 2353 / EN ISO 8434-1. On tightening, the cutting ring bites into the tube and creates a positive, force-fit, metal-sealing joint.

BENEFITS

- Reliable 24° cutting-ring joint to DIN 2353 / EN ISO 8434-1
- Detachable and reusable with consistent tightness
- Zinc/nickel or stainless steel surfaces for high corrosion protection

VERSION

Vormontagegestutzen 12S for SPR-PRC-H-M.

APPLICATIONS

Connection of hydraulic tubes in power units, machines and plant at high working pressures.